

Description

Crest PPC-76 is a liquid compound specifically formulated to process iron, galvanized steel, aluminum, and steel at low to medium temperature where a cleaner is required. It may be used in either a two stage, three stage, or a five stage washer system to provide improved paint adhesion and corrosion protection.

- » Color: White liquid free from any sediment.
- » Odor: Slight acidic odor.
- » Contains no molybdates or heavy metals.

Specifications

This product meets or exceeds all qualifications for the following:

- » Federal Specification TT-C-490F Type II Class A & B

Operating Data

3 Stage System

- » **Stage 1 Clean and Phosphate**
 - » **Product:** Crest PPC-76
 - » **Concentration:** 4 to 5% by volume (4 to 5 gallons/100 gallons water in tank)
 - » **pH:** 4.0 to 5.5
 - » **Temperature:** 110-160° F
 - » **Time:** 45 to 120 seconds
- » **Stage 2 Rinse**
 - » **Use:** Water-Overflowing
- » **Stage 3 Sealing Rinse**
 - » **Product:** Crest Inhibiseal (used as needed)
 - » **Concentration:** 1 pint per 100 gallons of water in tank
 - » **pH:** 4.5 to 5.0
 - » **Temperature:** Ambient
 - » **Time:** 30 to 45 seconds

Equipment

Mild steel is usually used for all tanks and heating equipment. Systems using this product usually are cleaned out every 3 to 6 months. Check with your salesman when this should be done.

Warranty and Liability Disclaimer

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience; however, since conditions of actual use are beyond our control, any recommendations, or suggestions, are made without warranty, expressed or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.